

CAT. N° 4 062 58



## AUXILIARY CHANGEOVER SWITCH DX<sup>3</sup> - 6 A 250 V~ - CONTACT POSITION - 0.5 MODULE

Pack (number of units)	1
Volume (dm <sup>3</sup> )	0,229
Weight (g)	50,00

### Product characteristics

#### Signalling auxiliaries prong busbar adapted

- To fit on the left-hand side of DX<sup>3</sup> and TX<sup>3</sup> devices
- Maximum number of auxiliaries per device:
  - 3 signalling auxiliaries or
  - 2 signalling auxiliaries + 1 remote tripping auxiliary
- Allow insertion of the supply busbar, top side
- No tool required for joining together the auxiliary and the main device.

#### Auxiliary contact

- 6 A - 250 V~ (changeover switch)
- For MCBs, RCBOs, RCCBs, isolating switches or remote trip isolating switches
- Indicates the position of the contacts of its associated device.
- Fault signalling contact
- 6 A - 250 V~ (changeover switch)
- For MCBs, RCBOs, RCCBs, isolating switches or remote trip isolating switches
- Indicates the position of the contacts of its associated device
- Number of modules : 0.5

### General characteristics

#### Signalling, remote tripping auxiliaries and motorised controls DX<sup>3</sup>

### Documentation

#### Catalogue pages & additional information

- [Description page \(p.072\)](#)
- [Dimensions of din-rail equipment](#)

#### Installation & technical data

- [F01222EN-03](#)

#### Installation instructions & related documents

- [LE04412AF](#)

#### Environmental product profile

- [Environnemental product sheet n°8 E0087A-FR](#)