

CAT. N° 4 062 62



AUXILIARY CHANGEOVER SWITCH DX³ - 6 A 250 V~ - EXCHANGEABLE - 0.5 MODULE

Pack (number of units)	1
Volume (dm ³)	0,229
Weight (g)	53,00

Product characteristics

Signalling auxiliaries prong busbar adapted

- To fit on the left-hand side of DX³ and TX³ devices
- Maximum number of auxiliaries per device:
 - 3 signalling auxiliaries or
 - 2 signalling auxiliaries + 1 remote tripping auxiliary
- Allow insertion of the supply busbar, top side
- No tool required for joining together the auxiliary and the main device.

Auxiliary contact

- 6 A - 250 V~ (changeover switch)
- For MCBs, RCBOs, RCCBs, isolating switches or remote trip isolating switches
- Indicates the position of the contacts of its associated device.
- Fault signalling contact
- 6 A - 250 V~ (changeover switch)
- For MCBs, RCBOs, RCCBs
- Allows the choice between the two functions
- Number of modules : 0.5

General characteristics

Signalling, remote tripping auxiliaries and motorised controls DX³

Documentation

Catalogue pages & additional information

- [Description page \(p.072\)](#)
- [Dimensions of din-rail equipment](#)

Installation & technical data

- [F01222EN-03](#)

Installation instructions & related documents

- [LE04412AE](#)

Environmental product profile

- [Environnemental product sheet n°8 E0087A-FR](#)