

CAT. N° 4 078 06



## MCB - DX³ 6000 - 10 kA - 2P - 230/400 V~ - 63 A - C CURVE

|                        |        |
|------------------------|--------|
| Pack (number of units) | 1      |
| Volume (dm³)           | 0,357  |
| Weight (g)             | 316,00 |

### Product characteristics

#### 2-pole 230/400 V~

- C curve
- Nominal rating  $I_n$  : 63 A
- Number of modules : 2

### General characteristics

#### MCBs DX³ 6000 - 10 kA - thermal magnetic circuit breakers from 1 A to 63 A - B and C curves

- Conform to IEC 60898-1
- Compatible with both, prong-type and fork type supply busbars
- Breaking capacity
  - 6000 - IEC 60898-1 - 400 V~
  - 10 kA - IEC 60947-2 - 400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries, motorised controls and add-on modules

### Documentation



#### Catalogue pages & additional information

- [Description page \(p.064\)](#)
- [Technical page \(p.074-075\)](#)
- [Dimensions of din-rail equipment](#)
- [Performance of MCBs and auxiliaries](#)



#### Agreements & certificates of conformity

- [OC / CB - IT-10651](#)
- [VDE - 40047508](#)
- [OC / CB - IT-10651/M1](#)
- [AENOR - 030/002456](#)
- [OC / CB - IT-18023](#)
- [VDE - 40034165](#)



#### Installation & technical data

- [F01591EN-02](#)



#### Environmental product profile

- [Environnemental product sheet n°8 E0112A-FR](#)