

CAT. N° 4 092 55



## MCB - DX<sup>3</sup> 10000 - 16 KA - 3P 400 V~ - 20 A - C CURVE

Pack (number of units)	1
Volume (dm <sup>3</sup> )	0,716
Weight (g)	415,00

### Product characteristics

#### 3-pole 400 V~

- C curve
- Nominal rating I<sub>n</sub> : 20 A
- Number of modules : 3

### General characteristics

#### MCBs DX<sup>3</sup> 10000 - 16 kA - thermal magnetic circuit breakers from 1 A to 125 A - B and C curves

- Conform to IEC 60898-1
- Compatible with prong-type and fork type supply busbars (except 80 A, 100 A and 125 A MCBs)
- Breaking capacity
  - 10000 - IEC 60898-1 - 400 V~
  - 16 kA - IEC 60947-2 - 400 V~
- Can be equipped with DX<sup>3</sup> signalling and remote tripping auxiliaries, motorised controls and add-on modules

### Documentation

#### Catalogue pages & additional information

- [Description page \(p.066\)](#)
- [Technical page \(p.074-075\)](#)
- [Dimensions of din-rail equipment](#)
- [Performance of MCBs and auxiliaries](#)

#### Agreements & certificates of conformity

- [VDE - 40034176](#)
- [OC / CB - IT - 14353](#)
- [OC / CB - IT-10652](#)
- [OC / CB - IT-10652/M2](#)
- [LOVAG - IT 14.019](#)
- [OC / CB - IT-10652/M1](#)
- [AENOR - Q30-002269](#)

#### Installation & technical data

- [F01559EN-03](#)

#### Environmental product profile

- [Environnemental product sheet n°8 E0112A-FR](#)